



## ■ 技术参数 Technical Specifications

型号Type	SC200/200EB		SC200/200EB-II
配置代号Configuration	BWM-3S	BWM-4S	BWM-4S
定位 Positioning	高效传动、智能版HLC、精英版操作台、升降机远程管理系统、变频控制、自动平层 High-efficiency transmission system, intelligent HLC, super control console, remote management system, frequency control, automatic leveling	高效传动、升降机远程管理系统、闭环变频控制、防坠落防溜车安全控制、精准平层、人脸识别、平稳运行 High-efficiency transmission system, remote management system, closed-loop frequency control, anti-falling and anti-sliding safety control, accurate automatic leveling, face identification, smooth running	高效传动、升降机远程管理系统、闭环变频控制、防坠落防溜车安全控制、精准平层、人脸识别、平稳运行 High-efficiency transmission system, remote management system, closed-loop frequency control, anti-falling and anti-sliding safety control, accurate automatic leveling, face identification, smooth running
额定载重量 (kg) Rated load	2×2000 (2×24人)	2×2000 (2×24人)	2×2000 (2×24人)
额定速度 (m/min) Rated speed	0~40	0~40	0~46
电机功率 (kW) Motor power	2×2×13	2×2×13	2×2×11/18.5 (50/87HZ)
减速机速比 Reduction gear ratio	1:16	1:16	1: 20.67
变频器功率 (kW) Frequency converter power	2×30	2×30	2×37
额定工作电流 (A) Rated current	2×2×27	2×2×27	2×2×36
电耗 (kVA) Power consumption	2×39	2×39	2×55
防坠安全器 Safety device type	SAJ40-1.2A	SAJ40-1.2A	SAJ40-1.2A
吊笼尺寸 (长×宽×高) Cage size(L×W×H)	3.2m×1.5m×2.5m	3.2m×1.5m×2.5m	3.2m×1.5m×2.5m
标准节尺寸 Size of mast section	650mm×650mm×1508mm	650mm×650mm×1508mm	650mm×650mm×1508mm
最大提升高度 (m) Maximum lifting height	500	500	500

■ 技术参数 Technical Specifications

型号Type	SC200/200BZ	
配置代号Configuration	BWM-3S	BWM-4S
定位 Positioning	高效传动、智能版HLC、精英版操作台、升降机远程管理系统、变频控制、自动平层 High-efficiency transmission system,intelligent HLC,super control console,remote management system,frequency control,automatic leveling	高效传动、升降机远程管理系统、闭环变频控制、防坠落防溜车安全控制、精准平层、人脸识别、平稳运行 High-efficiency transmission system,remote management system,closed-loop frequency control,anti-falling and anti-sliding safety control, accurate automatic leveling,face identification,smooth running
额定载重量 (kg) Rated load	2×2000 (2×24人)	2×2000 (2×24人)
额定速度 (m/min) Rated speed	0-63	0-63
电机功率 (kW) Motor power	2×3×9.2(NORD)	2×3×11/18.5 (50/87HZ)
减速机电速比 Reduction gear ratio	1:13.49	1:14.8
变频器功率 (kW) Frequency converter power	2×75	2×75
额定工作电流 (A) Rated current	2×3×32.6	2×3×36
电耗 (kVA) Power consumption	2×90	2×90
防坠安全器 Safety device type	SAJ50-1.4	SAJ50-1.4
吊笼尺寸(长×宽×高) Cage size(L×W×H)	3.2m×1.5m×2.5m	3.2m×1.5m×2.5m
标准节尺寸 Size of mast section	650mm×650mm×1508mm	650mm×650mm×1508mm
最大提升高度 (m) Maximum lifting height	500	500

■ 技术参数 Technical Specifications

型号Type	SC200/200BG
配置代号Configuration	BWM-3S
定位 Positioning	高效传动、智能版HLC、精英版操作台、升降机远程管理系统、变频控制、自动平层 High-efficiency transmission system,intelligent HLC,super control console,remote management system,frequency control,automatic leveling
额定载重量 (kg) Rated load	2×2000 (2×24人)
额定速度 (m/min) Rated speed	0-90
电机功率 (kW) Motor power	2×3×18.5 (NORD)
减速机电速比 Reduction gear ratio	1:11.4
变频器功率 (kW) Frequency converter power	2×132
额定工作电流 (A) Rated current	2×3×59.9
电耗 (kVA) Power consumption	2×156
防坠安全器 Safety device type	SAJ50-2.0
吊笼尺寸(长×宽×高) Cage size(L×W×H)	3.2m×1.5m×2.5m
标准节尺寸 Size of mast section	650mm×650mm×1508mm
最大提升高度 (m) Maximum lifting height	500